

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the Application:

Listing of Claims:

1. (currently amended) A back light assembly for applying light to a liquid crystal display panel, comprising:

a receiving container having a receiving space and a plate defining first and second [[a]] ledges extending at least partially about an upper periphery thereof,

the second ledge being disposed above the first ledge and having an inner edge generally coincident with or disposed outside of an outer edge of the first ledge such that the first and second ledges do not overlap;

a lamp disposed in the receiving space, for generating the light; and
~~a glass substrate interposed between the liquid crystal display panel and the lamp and having an outer periphery supported on the ledge of the receiving container plate; and,~~
a diffuser for diffusing the light generated by the lamp so as to make uniform a luminance distribution of the liquid crystal display panel.

2. (currently amended) The back light assembly of claim 21 [[1]], wherein the diffuser is a first diffusion sheet disposed on a first face of the glass substrate, the first face facing the liquid crystal display panel.

3. (original) The back light assembly of claim 2, wherein the first diffusion sheet comprises a first diffusion sheet body having an upper face and a lower face, and a light diffusion bead disposed on the upper face and the lower face.

4. (currently amended) The back light assembly of claim 21 [[1]], wherein a bottom face of the receiving container includes a substrate-supporting member for supporting the glass substrate.

5. (currently amended) The back light assembly of claim 21 [[1]], wherein the glass substrate comprises a first glass plate, a second glass plate and a second diffusion sheet interposed between the first glass plate and the second glass plate.

6. (original) The back light assembly of claim 5, wherein the second diffusion sheet comprises a second diffusion body and a light diffusion bead disposed on both faces of the second diffusion body.

7. (currently amended) The back light assembly of claim 21 [[1]], wherein the diffuser comprises a binder and a light diffusion bead mixed with the binder, the binder being disposed on a first face of the glass substrate, the first face facing the lamp.

8. (currently amended) The back light assembly of claim 21 [[1]], wherein the diffuser comprises a binder and a light diffusion bead mixed with the binder, the binder being disposed on a second face of the glass substrate, the second face facing the liquid crystal display panel.

9. (currently amended) The back light assembly of claim 21 [[1]], wherein the diffuser is an embossing pattern formed on a first face of the glass substrate, the first face facing the lamp.

10. (currently amended) The back light assembly of claim 21 [[1]], wherein the diffuser is an embossing pattern formed on a second face of the glass substrate, the second face facing the liquid crystal display panel.

11. (currently amended) The back light assembly of claim 21 [[1]], wherein the diffuser has a Haze value higher than about 90%.

12. (currently amended) The back light assembly of claim 21 [[1]], wherein the glass substrate comprises two glass plates, and the diffuser is an embossing pattern formed on at least one face of the two glass plates, the face being disposed between the two glass plates.

13. (currently amended) The back light assembly of claim 21 [[1]], wherein the glass substrate comprises a first glass plate, a second glass plate, a bead and a binder; the bead being mixed with the binder and interposed between the first glass plate and the second glass plate.

14. (currently amended) A liquid crystal display device, comprising:

a receiving container including a bottom face, a sidewall and a plate defining first and second [[a]] ledges extending at least partially about an upper periphery thereof, the bottom face and the sidewall forming a receiving space, and the second ledge being disposed above the first ledge and having an inner edge generally coincident with or disposed outside of an outer edge of

the first ledge such that the first and second ledges do not overlap;

a lamp disposed on the bottom face, for generating a first light;

~~a glass substrate disposed in the receiving space and having an outer periphery supported on the ledge of the receiving container plate, the first light advancing toward the glass substrate;~~

a diffusion plate including a diffuser for diffusing the first light so as to transform the first light into a second light having a more uniform luminance than the first light; and,

a liquid crystal display panel assembly having an outer periphery supported on the second ledge of the receiving container plate for displaying an image by using the second light.

15. (currently amended) The liquid crystal display device of claim 22 [[14]], wherein the diffuser is an embossing pattern formed on a first face of the glass substrate, the first face facing the lamp.

16. (currently amended) The liquid crystal display device of claim 22 [[14]], wherein the diffuser is an embossing pattern formed on a second face of the glass substrate, the second face facing the liquid crystal display panel.

17. (currently amended) The liquid crystal display device of claim 22 [[14]], wherein the diffuser is a diffusion sheet disposed on a second face of the glass substrate, the second face facing the liquid crystal display panel.

18. (original) The liquid crystal display device of claim 17, wherein the diffusion sheet comprises a diffusion sheet body and a light diffusion bead for diffusing the first light, the light diffusion bead being mixed with a binder and disposed on both face of the diffusion sheet body.

19. (currently amended) The liquid crystal display device of claim 22 [[14]], wherein the glass substrate comprises a first glass plate, a second glass plate, a bead and a binder; the bead being mixed with the binder and interposed between the first glass plate and the second glass plate.

20. (currently amended) The liquid crystal display device of claim 22 [[14]], wherein the glass substrate comprises two glass plates, and the diffuser is an embossing pattern formed on at least one face of the two glass plates, the face being disposed between the two glass plates.

Aug. 9. 2007, 12:25PM · MacPherson, Kwok, Chen & Heid
App. No. 16,519,529
Amendment dated Jun. 9, 2007
Reply to final Office action dated Mar. 9, 2007

No. 0729 P. 7
Docket No. AB-1400 US
(Ref. No. LW8035PC-US)

21. (New) The backlight assembly of claim 1, further comprising a glass substrate interposed between the liquid crystal display panel and the lamp and having an outer periphery supported on the first ledge of the receiving container plate.

22. (New) The liquid crystal display device of claim 14, further comprising a glass substrate disposed in the receiving space and having an outer periphery supported on the first ledge of the receiving container plate, the first light advancing toward the glass substrate.